

Sidro B A4



→ Nehrđajući čelik A4

→ Odobren za nenapukli beton

→ Tri dubine sidrenja

Opis	Ref. br.	Debljina pričvrstnog elementa t _{fix} mm	Standardna dubina sidrenja		Minimalna dubina sidrenja		Maksimalna dubina sidrenja		Dubina provrta h ₁ mm	Duljina sidra l mm	Navoj mm	Pak. sadr. Kom.	Tež. po pak. kg
			Debljina pričvrstnog elementa t _{fix2} mm	Dubina sidrenja h _{ef2} mm	Debljina pričvrstnog elementa t _{fix1} mm	Dubina sidrenja h _{ef1} mm	Debljina pričvrstnog elementa t _{fix3} mm	Dubina sidrenja h _{ef3} mm					
B 6-5/40 A4 ¹⁾	01005501	6	-	-	5	18	-	-	h _{ef} + 9	40	M6x16	100	1,06
B 6-5/52 A4	01006501	6	-	-	5	30	-	-	h _{ef} + 9	52	M6x20	100	1,27
B 6-10-20/67 A4	01010501	6	10	40	20	30	-	-	h _{ef} + 9	67	M6x30	100	1,56
B 6-25-35/82 A4	01015501	6	25	40	35	30	5	60	h _{ef} + 9	82	M6x35	100	1,80
B 6-40-50/97 A4	01025501	6	40	40	50	30	20	60	h _{ef} + 9	97	M6x35	100	2,08
B 8-5/50 A4 ¹⁾	01105501	8	-	-	5	24	-	-	h _{ef} + 11	50	M8x22	100	2,34
B 8-4/60 A4	01110501	8	-	-	4	35	-	-	h _{ef} + 12	60	M8x25	100	2,64
B 8-10-19/75 A4	01115501	8	10	44	19	35	-	-	h _{ef} + 12	75	M8x40	100	3,10
B 8-15-24/80 A4	01120501	8	15	44	24	35	-	-	h _{ef} + 12	80	M8x45	100	3,28
B 8-20-29/85 A4	01125501	8	20	44	29	35	-	-	h _{ef} + 12	85	M8x50	100	3,42
B 8-30-39/95 A4	01135501	8	30	44	39	35	4	70	h _{ef} + 12	95	M8x60	100	3,73
B 8-45-54/110 A4	01145501	8	45	44	54	35	19	70	h _{ef} + 12	110	M8x75	100	4,20
B 8-55-64/120 A4	01150501	8	55	44	64	35	29	70	h _{ef} + 12	120	M8x85	100	4,57
B 10-10/60 A4 ¹⁾	01205501	10	-	-	10	25	-	-	h _{ef} + 15	60	M10x25	50	2,30
B 10-10-16/85 A4	01210501	10	10	48	16	42	-	-	h _{ef} + 14	85	M10x40	50	2,85
B 10-15-21/90 A4	01215501	10	15	48	21	42	-	-	h _{ef} + 14	90	M10x45	50	2,97
B 10-20-26/95 A4	01220501	10	20	48	26	42	-	-	h _{ef} + 14	95	M10x50	50	3,10
B 10-30-36/105 A4	01225501	10	30	48	36	42	-	-	h _{ef} + 14	105	M10x60	50	3,33
B 10-45-51/120 A4	01230501	10	45	48	51	42	13	80	h _{ef} + 14	120	M10x75	50	3,75
B 10-50-56/125 A4	01235501	10	50	48	56	42	18	80	h _{ef} + 14	125	M10x80	50	3,87
B 10-70-76/145 A4	01240501	10	70	48	76	42	38	80	h _{ef} + 14	145	M10x80	50	4,38
B 10-100-106/175 A4	01245501	10	100	48	106	42	68	80	h _{ef} + 14	175	M10x80	50	5,15
B 10-140-146/215 A4	01250501	10	140	48	146	42	108	80	h _{ef} + 14	215	M10x80	25	3,10
B 12-5/75 A4 ¹⁾	01305501	12	-	-	5	38	-	-	h _{ef} + 17	75	M12x30	25	1,96
B 12-14/95 A4	01310501	12	-	-	14	50	-	-	h _{ef} + 17	95	M12x50	25	2,33
B 12-10-25/105 A4	01312501	12	10	65	25	50	-	-	h _{ef} + 17	105	M12x60	25	2,53
B 12-15-30/110 A4	01315501	12	15	65	30	50	-	-	h _{ef} + 17	110	M12x65	25	2,62
B 12-20-35/115 A4	01320501	12	20	65	35	50	-	-	h _{ef} + 17	115	M12x70	25	2,70
B 12-30-45/125 A4	01325501	12	30	65	45	50	-	-	h _{ef} + 17	125	M12x80	25	2,88
B 12-50-65/145 A4	01330501	12	50	65	65	50	15	100	h _{ef} + 17	145	M12x100	25	3,28
B 12-65-80/160 A4	01335501	12	65	65	80	50	30	100	h _{ef} + 17	160	M12x100	25	3,55
B 12-85-100/180 A4	01340501	12	85	65	100	50	50	100	h _{ef} + 17	180	M12x100	25	3,90
B 12-105-120/200 A4	01345501	12	105	65	120	50	70	100	h _{ef} + 17	200	M12x100	25	4,28
B 12-145-160/240 A4	01355501	12	145	65	160	50	110	100	h _{ef} + 17	240	M12x80	20	4,39
B 16-5/90 A4 ¹⁾	01505501	16	-	-	5	47	-	-	h _{ef} + 18	90	M16x35	20	3,37
B 16-14/115 A4	01510501	16	-	-	14	64	-	-	h _{ef} + 20	115	M16x60	20	3,98
B 16-10-26/130 A4	01512501	16	10	80	26	64	-	-	h _{ef} + 20	130	M16x70	20	4,34
B 16-30-46/150 A4	01515501	16	30	80	46	64	-	-	h _{ef} + 20	150	M16x90	20	4,87
B 16-60-76/180 A4	01520501	16	60	80	76	64	22	120	h _{ef} + 20	180	M16x110	20	5,66
B 16-100-116/220 A4	01530501	16	100	80	116	64	62	120	h _{ef} + 20	220	M16x80	10	3,59
B 16-130-146/250 A4	01535501	16	130	80	146	64	92	120	h _{ef} + 20	250	M16x80	10	3,99
B 16-200-216/320 A4	01545501	16	200	80	216	64	162	120	h _{ef} + 20	320	M16x80	10	5,16
B 20-5-27/150 A4	01605501	20	5	100	27	78	-	-	h _{ef} + 21	150	M20x70	10	3,86
B 20-35-57/180 A4	01610501	20	35	100	57	78	20	115	h _{ef} + 21	180	M20x70	10	4,47
B 20-60-82/205 A4	01612501	20	60	100	82	78	45	115	h _{ef} + 21	205	M20x70	10	5,03
B 20-95-117/240 A4	01615501	20	95	100	117	78	80	115	h _{ef} + 21	240	M20x70	10	6,26

¹⁾Nije dio odobrenja.

Sidro B HCR



→ Nehrđajući čelik 1.4529

→ Odobren za spuštene stropove

Opis	Ref. br.	Debljina pričvrstnog elementa t _{fix} mm	Standardna dubina sidrenja		Minimalna dubina sidrenja		Maksimalna dubina sidrenja		Dubina provrta h ₁ mm	Duljina sidra l mm	Navoj mm	Pak. sadr. Kom.	Tež. po pak. kg
			Debljina pričvrstnog elementa t _{fix2} mm	Dubina sidrenja h _{ef2} mm	Debljina pričvrstnog elementa t _{fix1} mm	Dubina sidrenja h _{ef1} mm	Debljina pričvrstnog elementa t _{fix3} mm	Dubina sidrenja h _{ef3} mm					
B 6-0-10/57 HCR	01007651	6	0	40	10	30	-	-	h _{ef} + 9	57	M6x20	100	1,58
B 6-10-20/67 HCR	01010651	6	10	40	20	30	-	-	h _{ef} + 9	67	M6x20	100	1,78
B 6-25-35/82 HCR	01015651	6	25	40	35	30	5	60	h _{ef} + 9	82	M6x20	100	2,13
B 6-40-50/97 HCR	01025651	6	40	40	50	30	20	60	h _{ef} + 9	97	M6x20	100	2,35

Ostale dužine na zahtjev.

